

SAFETY DATA SHEET

SPECIALTY ELECTRONIC MATERIALS UK LIMITED

Safety Data Sheet according to Regulation (EC) No 1907/2006 - Annex II

Product name: FROTH-PAK™ Foam Systems 180 QR POLYOL

Revision Date: 25.05.2022 Version: 1.0

Date of last issue: -Print Date: 25.07.2022

SPECIALTY ELECTRONIC MATERIALS UK LIMITED encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name: FROTH-PAK™ Foam Systems 180 QR POLYOL

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Component for polyurethane manufacture. Thermal insulation.

1.3 Details of the supplier of the safety data sheet COMPANY IDENTIFICATION

SPECIALTY ELECTRONIC MATERIALS UK LIMITED KINGS COURT, LONDON ROAD STEVENAGE England SG1 2NG UNITED KINGDOM

Customer Information Number: 00800-3876-6838

SDSQuestion-EU@dupont.com

1.4 EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: +(44)-870-8200418 **Local Emergency Contact:** +(44)-870-8200418

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008:

Gases under pressure - Liquefied gas - H280 Acute toxicity - Category 4 - Oral - H302 Eye irritation - Category 2 - H319 Skin sensitisation - Category 1 - H317

For the full text of the H-Statements mentioned in this Section, see Section 16.

Revision Date: 25.05.2022 Version: 1.0

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

Hazard pictograms





Signal word: WARNING

Hazard statements

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Precautionary statements

P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ eye protection/ face protection.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Contains Reaction products of phosphoryl trichloride and 2-methyloxirane; triethyl phosphate; 2,2'-

oxybisethanol; Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

2.3 Other hazards

Endocrine disrupting properties (human health):

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties (environment):

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

PBT and vPvB assessment:

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Revision Date: 25.05.2022 Version: 1.0

3.2 Mixtures

This product is a mixture.

Identification number	Component	Classification according to Regulation (EU) 1272/2008 (CLP)	specific concentration limit/ M-Factors/ Acute toxicity estimate	%
CASRN 1244733-77-4 EC-No. - Index-No. - REACH No 01-2119486772-26	Reaction products of phosphoryl trichloride and 2-methyloxirane	Acute Tox. 4 - H302	Oral ATE: 632 mg/kg Inhalation ATE: > 7 mg/l (dust/mist) Dermal ATE: > 2,000 mg/kg	> 10.0 - < 20.0 %
CASRN 102687-65-0 EC-No. 700-486-0 Index-No. - REACH No 01-2119855084-38	trans-1-Chloro-3,3,3- trifluoropropene	Press. Gas Liquefied gas - H280 Aquatic Chronic 3 - H412	Inhalation ATE: 120000 ppm (gas)	> 10.0 - < 25.0 %
CASRN 78-40-0 EC-No. 201-114-5 Index-No. 015-013-00-7 REACH No 01-2119492852-28	triethyl phosphate	Acute Tox. 4 - H302 Eye Irrit. 2 - H319	Oral ATE: 1,131 mg/kg Dermal ATE: > 21,400 mg/kg	> 5.0 - < 10.0 %
CASRN 111-46-6 EC-No. 203-872-2 Index-No. 603-140-00-6 REACH No 01-2119457857-21	2,2'-oxybisethanol	Acute Tox. 4 - H302	Oral ATE: 500 mg/kg Inhalation ATE: > 4.6 mg/l (dust/mist) Dermal ATE: 13,330 mg/kg	> 5.0 - < 10.0 %
CASRN 3164-85-0 EC-No. 221-625-7 Index-No. - REACH No 01-2119980714-29	2-Ethylhexanoic acid potassium salt	Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Repr. 2 - H361fd	Oral ATE: 2,043 mg/kg Inhalation ATE: > 0.11 mg/l (dust/mist) Dermal ATE: > 2,000 mg/kg	> 1.0 - < 3.0 %
CASRN 124-38-9 EC-No. 204-696-9 Index-No. - REACH No	Carbon dioxide	Press. Gas Liquefied gas - H280	Inhalation ATE: 58750 ppm (gas)	> 1.0 - < 5.0 %
CASRN	Bis[(2-ethyl-2,5-	Acute Tox. 4 - H302	Oral ATE: 892 mg/kg	> 0.1 - < 1.0 %

Revision Date: 25.05.2022

Version: 1.0

	dimethylhexanoyl)oxy](dime		
EC-No.	thyl)stannane	Skin Sens. 1A - H317	
273-028-6		Aquatic Chronic 3 - H412	
Index-No.			
_			
REACH No			
_			

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be available in work area.

Eye contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

4.2 Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

4.3 Indication of any immediate medical attention and special treatment needed Notes to physician: Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Revision Date: 25.05.2022 Version: 1.0

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: Do not use direct water stream. May spread fire.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Hydrogen halides.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Blowing agent vaporizes quickly at room temperature. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

5.3 Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Keep personnel out of confined or poorly ventilated areas. Keep upwind of spill. Ventilate area of leak or spill. Confined space entry procedures must be followed before entering the area. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.
- 6.2 Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.
- 6.3 Methods and materials for containment and cleaning up: Contain spilled material if possible. Absorb with materials such as: Dirt. Sand. Sawdust. Collect in suitable and properly labeled containers. Wash the spill site with water. See Section 13, Disposal Considerations, for additional information.

Revision Date: 25.05.2022 Version: 1.0

6.4 Reference to other sections: References to other sections, if applicable, have been provided in the previous sub-sections.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling: Do not enter confined spaces unless adequately ventilated. Avoid contact with eyes. Avoid breathing vapor. Wash thoroughly after handling. Use with adequate ventilation. Keep container closed. This material is hygroscopic in nature. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

7.2 Conditions for safe storage, including any incompatibilities: Store in a dry place. Avoid prolonged exposure to heat and air. Protect from atmospheric moisture. Blowing agent may migrate from product and accumulate in some storage situations. Elevated temperatures can cause pressure buildup in closed containers due to the release of blowing agents. See Section 10 for more specific information.

Storage stability

Storage temperature: Storage Period: 5 - 30 °C 15 Month

7.3 Specific end use(s): Information on specific end use(s) of this product may be provided in a technical data sheet/annex to the SDS (if available).

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
trans-1-Chloro-3,3,3-	US WEEL	TWA	800 ppm
trifluoropropene			
triethyl phosphate	US WEEL	TWA	7.45 mg/m3
2,2'-oxybisethanol	US WEEL	TWA	10 mg/m3
	GB EH40	TWA	101 mg/m3 23 ppm
	Further information: 2: Whe three times the long-term ex	ere no specific short-term expo xposure should be used	osure limit is listed, a figure
Carbon dioxide	ACGIH	TWA	5,000 ppm
	ria: Asphyxia		
	ACGIH	STEL	30,000 ppm
Further information: asphyxia: Asphyxia		ria: Asphyxia	
	2006/15/EC	TWA	9,000 mg/m3 5,000
			ppm
	Further information: Indicat	ive	
	GB EH40	STEL	27,400 mg/m3 15,000
			ppm
	GB EH40	TWA	9,150 mg/m3 5,000
			ppm

Revision Date: 25.05.2022 Version: 1.0

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane	ACGIH	TWA	0.1 mg/m3 , Tin
	Further information: A4: No cutaneous absorption	t classifiable as a human car	cinogen; Skin: Danger of
	ACGIH	STEL	0.2 mg/m3 , Tin
	Further information: A4: No cutaneous absorption	t classifiable as a human car	cinogen; Skin: Danger of
	GB EH40	TWA	0.1 mg/m3 , Tin
			The assigned substances are on will lead to systemic toxicity.
	GB EH40	STEL	0.2 mg/m3 , Tin
			The assigned substances are on will lead to systemic toxicity.

Derived No Effect Level

2,2'-oxybisethanol

Workers

Acute systemic effects		Acute loc	Acute local effects		Long-term systemic effects		Long-term local effects	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	
n.a.	n.a.	n.a.	n.a.	106 mg/kg bw/day	n.a.	n.a.	60 mg/m3	

Consumers

Acute systemic effects		Acute loc	cute local effects		Long-term systemic effects		Long-term local effects		
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	53 mg/kg	n.a.	n.a.	n.a.	12
					bw/day				mg/m3

Predicted No Effect Concentration

2,2'-oxybisethanol

Compartment	PNEC
Fresh water	10 mg/l
Marine water	1 mg/l
Intermittent use/release	10 mg/l
Sewage treatment plant	199.5 mg/l
Fresh water sediment	20.9 mg/kg
Soil	1.53 mg/kg
Marine sediment	2.09 mg/kg

8.2 Exposure controls

Engineering controls: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only in enclosed systems or with local exhaust ventilation. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent.

Page 7 of 28

Revision Date: 25.05.2022 Version: 1.0

Skin protection

Hand protection: Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Styrene/butadiene rubber. Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. When respiratory protection is required, use an approved positive-pressure self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply. Use NIOSH approved respiratory protection.

Environmental exposure controls

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state liquid

Form

Liquefied gas

Colour Yellowish-white

Odour characteristic

Odour Threshold
No test data available

Page 8 of 28

Revision Date: 25.05.2022 Version: 1.0

Melting point/freezing point Freezing point: not determined

Melting point/range: not determined

Boiling point or initial boiling point and boiling range

Boiling point/boiling range: No data available

Flammability No data available

Lower explosion limit and upper explosion limit / flammability limit

Lower explosion limit / Lower flammability limit

Not applicable

Upper explosion limit / Upper flammability limit

Not applicable

Flash point Not applicable

Auto-ignition temperature not flammable

Decomposition temperature Thermal decomposition

No test data available

pH Not applicable

Viscosity, kinematic

No data available

Solubility(ies) Water solubility

immiscible

Partition coefficient: n-

octanol/water

No data available

Vapour pressure Container is under pressure.

Density and / or relative

density

Relative Density (water = 1)

No data available

Relative vapour density not determined

Particle characteristics Not applicable

9.2 Other information

Explosives Not applicable

Oxidizing properties

Revision Date: 25.05.2022 Version: 1.0

No data available

Substances and mixtures, which in contact with water, emit flammable gases

The substance or mixture does not emit flammable gases

in contact with water.

Evaporation rate not determined

NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10: STABILITY AND REACTIVITY

- 10.1 Reactivity: No data available
- 10.2 Chemical stability: Stable under recommended storage conditions. See Storage, Section 7.
- 10.3 Possibility of hazardous reactions: Will not occur by itself.
- **10.4 Conditions to avoid:** Product can oxidize at elevated temperatures. Elevated temperatures can cause pressure buildup in closed containers due to the release of blowing agents. Generation of gas during decomposition can cause pressure in closed systems.
- **10.5 Incompatible materials:** Avoid contact with oxidizing materials. Avoid contact with: Strong acids. Strong bases. Avoid unintended contact with isocyanates. The reaction of polyols and isocyanates generates heat.
- **10.6 Hazardous decomposition products:** Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Carbon dioxide. Alcohols. Ethers. Hydrocarbons. Hydrogen halides. Ketones. Polymer fragments.

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Acute toxicity (Acute oral toxicity)

Acute toxicity, Category 4 H302: Harmful if swallowed.

Classification procedure: Calculation method

Acute toxicity estimate, 1,908 mg/kg Calculation method

Acute toxicity (Acute dermal toxicity)

Not classified

Not classified due to lack of data. / Not classified due to data which are conclusive although

Revision Date: 25.05.2022 Version: 1.0

insufficient for classification.

Product test data not available. Refer to component data.

Acute toxicity (Acute inhalation toxicity)

Not classified

Not classified due to lack of data. / Not classified due to data which are conclusive although insufficient for classification.

Product test data not available. Refer to component data.

Skin corrosion/irritation

Not classified

Not classified due to lack of data. / Not classified due to data which are conclusive although insufficient for classification.

Product test data not available. Refer to component data.

Serious eye damage/eye irritation

Eye irritation, Category 2

H319: Causes serious eye irritation.

Classification procedure: Calculation method

Product test data not available. Refer to component data.

Respiratory or skin sensitisation

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

Classification procedure: Calculation method

Product test data not available. Refer to component data.

Germ cell mutagenicity

Not classified

Not classified due to lack of data. / Not classified due to data which are conclusive although insufficient for classification.

Product test data not available. Refer to component data.

Carcinogenicity

Not classified

Not classified due to lack of data. / Not classified due to data which are conclusive although insufficient for classification.

Product test data not available. Refer to component data.

Reproductive toxicity

Not classified

Not classified due to lack of data. / Not classified due to data which are conclusive although insufficient for classification.

Page 11 of 28

Revision Date: 25.05.2022 Version: 1.0

Toxicity to reproduction assessment:

Product test data not available. Refer to component data.

Assessment Teratogenicity:

Product test data not available. Refer to component data.

STOT - single exposure

Not classified

Not classified due to lack of data. / Not classified due to data which are conclusive although insufficient for classification.

Product test data not available. Refer to component data.

STOT - repeated exposure

Not classified

Not classified due to lack of data. / Not classified due to data which are conclusive although insufficient for classification.

Product test data not available. Refer to component data.

Aspiration Hazard

Not classified

Not classified due to lack of data. / Not classified due to data which are conclusive although insufficient for classification.

Product test data not available. Refer to component data.

COMPONENTS INFLUENCING TOXICOLOGY:

Reaction products of phosphoryl trichloride and 2-methyloxirane

Acute toxicity (Acute oral toxicity)

LD50, Rat, 632 mg/kg EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)

Acute toxicity (Acute dermal toxicity)

LD50, Rat, > 2,000 mg/kg OECD Test Guideline 402 No deaths occurred at this concentration.

Acute toxicity (Acute inhalation toxicity)

LC50, Rat, 4 Hour, dust/mist, > 7 mg/l OECD Test Guideline 403

Skin corrosion/irritation

Brief contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

May cause lacrimation (tears).

Essentially nonirritating to eyes.

Respiratory or skin sensitisation

Did not demonstrate the potential for contact allergy in mice.

For respiratory sensitization:

No relevant information found.

Page 12 of 28

Revision Date: 25.05.2022 Version: 1.0

Germ cell mutagenicity

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

Carcinogenicity

No data available.

Reproductive toxicity

Toxicity to reproduction assessment:

In animal studies, did not interfere with reproduction.

Assessment Teratogenicity:

Did not cause birth defects in laboratory animals.

STOT - single exposure

The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

Aspiration Hazard

Based on available information, aspiration hazard could not be determined.

trans-1-Chloro-3,3,3-trifluoropropene

Acute toxicity (Acute oral toxicity)

Single dose oral LD50 has not been determined.

Acute toxicity (Acute dermal toxicity)

The dermal LD50 has not been determined.

Acute toxicity (Acute inhalation toxicity)

LC50, Rat, 4 Hour, gas, 120000 ppm

Skin corrosion/irritation

Brief contact is essentially nonirritating to skin.

Serious eye damage/eye irritation

No relevant data found.

Respiratory or skin sensitisation

Did not cause allergic skin reactions when tested in humans.

For respiratory sensitization:

No relevant data found.

Germ cell mutagenicity

This material was not mutagenic in an Ames bacterial assay.

Carcinogenicity

No relevant data found.

Revision Date: 25.05.2022 Version: 1.0

Reproductive toxicity

Toxicity to reproduction assessment:

No relevant data found.

Assessment Teratogenicity:

No relevant data found.

STOT - single exposure

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

STOT - repeated exposure

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Aspiration Hazard

Based on available information, aspiration hazard could not be determined.

triethyl phosphate

Acute toxicity (Acute oral toxicity)

LD50, Rat, 1,131 mg/kg

Acute toxicity (Acute dermal toxicity)

LD50, Guinea pig, > 21,400 mg/kg

Skin corrosion/irritation

Prolonged contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

May cause moderate eye irritation.

May cause slight corneal injury.

Respiratory or skin sensitisation

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Germ cell mutagenicity

In vitro genetic toxicity studies were predominantly negative. Animal genetic toxicity studies were predominantly negative.

Carcinogenicity

No relevant data found.

Reproductive toxicity

Toxicity to reproduction assessment:

In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals.

Assessment Teratogenicity:

No relevant data found.

Product name: FROTH-PAK™ Foam Systems 180 QR POLYOL **Revision Date: 25.05.2022**

Version: 1.0

STOT - single exposure

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

STOT - repeated exposure

Triethyl phosphate is considered to be a weak cholinesterase inhibitor. Excessive exposure may produce organophosphate type cholinesterase inhibition. Signs and symptoms of excessive exposure may be headache, dizziness, incoordination, muscle twitching, tremors, nausea, abdominal cramps, diarrhea, sweating, pinpoint pupils,

blurred vision, salivation, tearing, tightness in chest, excessive urination, convulsions.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

2,2'-oxybisethanol

Acute toxicity (Acute oral toxicity)

In humans, expected to be moderately toxic if swallowed even though oral toxicity was low when tested in animals. Ingestion of quantities (approximately 65 mL (2 oz.) for diethylene glycol or 100 mL (3 oz.) for ethylene glycol) has caused death in humans. May cause nausea and vomiting. May cause abdominal discomfort or diarrhea. Excessive exposure may cause central nervous system effects, cardiopulmonary effects (metabolic acidosis), and kidney failure. LD50, Rat, male, 19,600 mg/kg

Lethal Dose, Human, adult, 65 ml Estimated.

Acute toxicity estimate, 500 mg/kg Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Acute toxicity (Acute dermal toxicity)

LD50, Rabbit, 13,330 mg/kg

Acute toxicity (Acute inhalation toxicity)

LC50, Rat, 4 Hour, dust/mist, > 4.6 mg/l The LC50 value is greater than the Maximum Attainable Concentration. No deaths occurred at this concentration.

Skin corrosion/irritation

Prolonged contact is essentially nonirritating to skin.

Serious eve damage/eve irritation

May cause slight temporary eye irritation.

Corneal injury is unlikely.

Respiratory or skin sensitisation

Did not cause allergic skin reactions when tested in humans. Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Germ cell mutagenicity

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Page 15 of 28

Revision Date: 25.05.2022 Version: 1.0

Carcinogenicity

Diethylene glycol has been tested for carcinogenicity in animal studies and is not believed to pose a carcinogenic risk to man.

Reproductive toxicity

Toxicity to reproduction assessment:

Diethylene glycol did not interfere with reproduction in animal studies except at very high doses.

Assessment Teratogenicity:

Diethylene glycol has caused toxicity to the fetus and some birth defects at maternally toxic, high doses in animals. Other animal studies have not reproduced birth defects even at much higher doses that caused severe maternal toxicity.

STOT - single exposure

The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

Aspiration Hazard

No aspiration toxicity classification

2-Ethylhexanoic acid potassium salt

Acute toxicity (Acute oral toxicity)

Information given is based on data obtained from similar substances. LC50, Rat, 2,043 mg/kg **OECD Test Guideline 401**

Acute toxicity (Acute dermal toxicity)

Information given is based on data obtained from similar substances. LD50, Rabbit, > 2,000 mg/kg OECD Test Guideline 402

Acute toxicity (Acute inhalation toxicity)

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration. LC0, Rat, 4 Hour, dust/mist, > 0.11 mg/l OECD Test Guideline 403

Skin corrosion/irritation

Brief contact may cause severe skin irritation with pain and local redness.

Serious eye damage/eye irritation

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Respiratory or skin sensitisation

Did not cause allergic skin reactions when tested in guinea pigs. Information given is based on data obtained from similar substances.

No data available

Revision Date: 25.05.2022

Version: 1.0

Germ cell mutagenicity

Animal genetic toxicity studies were negative. In vitro genetic toxicity studies were negative. Information given is based on data obtained from similar substances.

Carcinogenicity

No data available

Reproductive toxicity

Toxicity to reproduction assessment:

In animal studies, has been shown to interfere with fertility. Information given is based on data obtained from similar substances.

Assessment Teratogenicity:

Has caused birth defects in laboratory animals. Information given is based on data obtained from similar substances.

STOT - single exposure

The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Information given is based on data obtained from similar substances.

Aspiration Hazard

No aspiration toxicity classification

Carbon dioxide

Acute toxicity (Acute oral toxicity)

Single dose oral LD50 has not been determined.

Acute toxicity (Acute dermal toxicity)

The dermal LD50 has not been determined.

Acute toxicity (Acute inhalation toxicity)

LC50, Rat, 4 hrs, gas, 58750 ppm

Skin corrosion/irritation

No hazard from gas.

Skin contact with the solid ("dry ice") may cause frostbite.

Liquid may cause frostbite upon skin contact.

Serious eye damage/eye irritation

No hazard from gas.

Eye contact with the solid ("dry ice") may cause freeze burns.

Liquid may cause frostbite.

Respiratory or skin sensitisation

No relevant data found.

For respiratory sensitization:

No relevant data found.

Revision Date: 25.05.2022

Version: 1.0

Germ cell mutagenicity

No relevant data found.

Carcinogenicity

Available data are inadequate to evaluate carcinogenicity.

Reproductive toxicity

Toxicity to reproduction assessment:

Available data are inadequate to determine effects on reproduction.

Assessment Teratogenicity:

Available data are inadequate for evaluation of potential to cause birth defects.

STOT - single exposure

Available data are inadequate to determine single exposure specific target organ toxicity.

STOT - repeated exposure

Experiments with humans and animals suggest that continued exposure to 1.5% carbon dioxide may alter physiological processes, such as acid-base and electrolyte balance in the blood, calcium-phosphorus metabolism, and neuroendrocrine activity.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Acute toxicity (Acute oral toxicity)

LD50, Rat, 892 mg/kg

Acute toxicity (Acute dermal toxicity)

The dermal LD50 has not been determined.

Acute toxicity (Acute inhalation toxicity)

The LC50 has not been determined.

Skin corrosion/irritation

Brief contact may cause skin irritation with local redness.

Serious eye damage/eye irritation

May cause slight temporary eye irritation.

Respiratory or skin sensitisation

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Germ cell mutagenicity

Not mutagenic in Ames Test

Carcinogenicity

No relevant data found.

Page 18 of 28

Revision Date: 25.05.2022 Version: 1.0

Reproductive toxicity

Toxicity to reproduction assessment:

No relevant data found.

Assessment Teratogenicity:

No relevant data found.

STOT - single exposure

Available data are inadequate to determine single exposure specific target organ toxicity.

STOT - repeated exposure

No relevant information found.

Aspiration Hazard

No aspiration toxicity classification

11.2. Information on other hazards

Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

No data available

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

12.1 Toxicity

Reaction products of phosphoryl trichloride and 2-methyloxirane

Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (10 <

LC50/EC50/IC50/LL50/EL50 <= 100 mg/L and NOEC > 1mg/l in the most sensitive species).

LC50, Pimephales promelas (fathead minnow), 96 Hour, 51 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 131 mg/l

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, 82 mg/l, OECD Test Guideline

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, 13 mg/l, OECD Test Guideline 201

Chronic toxicity to aquatic invertebrates

Revision Date: 25.05.2022 Version: 1.0

NOEC, Daphnia magna (Water flea), 21 d, 32 mg/l

trans-1-Chloro-3,3,3-trifluoropropene

Acute toxicity to fish

Material is harmful to aquatic organisms (LC50/EC50/IC50 between 10 and 100 mg/L in the most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), Static, 96 Hour, 38 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna, 48 Hour, 82 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aguatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth inhibition, 106.7 mg/l NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate, 115 mg/l

triethyl phosphate

Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Leuciscus idus (Golden orfe), static test, 48 Hour, 2,140 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 350 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

EC50, Desmodesmus subspicatus (green algae), 72 Hour, Growth rate inhibition, 900 mg/l, **OECD Test Guideline 201**

Toxicity to bacteria

EC50, activated sludge, Respiration inhibition, 30 min, > 2,985 mg/l, OECD 209 Test

2.2'-oxybisethanol

Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 75,200 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 24 Hour, > 10,000 mg/l

Acute toxicity to algae/aguatic plants

Based on data from similar materials

EC50, Selenastrum capricornutum (green algae), 96 Hour, 6,500 - 13,000 mg/l

Toxicity to bacteria

EC50, activated sludge, 3 Hour, > 1,000 mg/l, OECD 209 Test

Chronic toxicity to fish

Based on data from similar materials

Revision Date: 25.05.2022 Version: 1.0

NOEC, Pimephales promelas (fathead minnow), 7 d, 15,380 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, > 15,000 mg/l

2-Ethylhexanoic acid potassium salt

Acute toxicity to fish

Information given is based on data obtained from similar substances.

LC50, Oryzias latipes (Orange-red killifish), 96 Hour, > 100 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

Information given is based on data obtained from similar substances.

EC50, Daphnia magna (Water flea), 48 Hour, 85.4 mg/l

Acute toxicity to algae/aguatic plants

Information given is based on data obtained from similar substances. EC50, Desmodesmus subspicatus (green algae), 96 Hour, 49.3 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, 25 mg/l

Carbon dioxide

Acute toxicity to fish

May decrease pH of aquatic systems to < pH 5 which may be toxic to aquatic organisms. LC0, Oncorhynchus mykiss (rainbow trout), 1 Hour, 240 mg/l, Method Not Specified.

Acute toxicity to aquatic invertebrates

Based on data from similar materials

NOEC, Daphnia magna (Water flea), 48 Hour, > 100 mg/l

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Acute toxicity to aquatic invertebrates

Material is toxic to aquatic organisms (LC50/EC50/IC50 between 1 and 10 mg/L in the most sensitive species).

EC50, Daphnia magna (Water flea), 48 Hour, 39 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aguatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, 7.6 mg/l, OECD Test Guideline

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, 1.2 mg/l, OECD Test Guideline 201

Toxicity to bacteria

For similar material(s):

EC50, Bacteria, 3 Hour, Respiration rates., 14 mg/l

12.2 Persistence and degradability

Reaction products of phosphoryl trichloride and 2-methyloxirane

Biodegradability: Material is not readily biodegradable according to OECD/EEC guidelines.

Biodegradation: 14 % Exposure time: 28 d

Page 21 of 28

Product name: FROTH-PAK™ Foam Systems 180 QR POLYOL Revision Date: 25.05.2022 Version: 1.0

Method: OECD Test Guideline 301E

trans-1-Chloro-3,3,3-trifluoropropene

Biodegradability: Material is not readily biodegradable according to OECD/EEC guidelines.

Biodegradation: 0 % **Exposure time:** 28 d

Method: OECD Test Guideline 301D

triethyl phosphate

Biodegradability: Material is ultimately biodegradable (reaches > 70% mineralization in

OECD test(s) for inherent biodegradability).

10-day Window: Not applicable **Biodegradation:** > 90 % **Exposure time:** 28 d

Method: OECD Test Guideline 302B or Equivalent

2,2'-oxybisethanol

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready

biodegradability. 10-day Window: Pass **Biodegradation:** 90 - 100 %

Expenses times 20 d

Exposure time: 20 d

Method: OECD Test Guideline 301A or Equivalent

10-day Window: Not applicable **Biodegradation:** 82 - 98 %

Exposure time: 28 d

Method: OECD Test Guideline 302C or Equivalent

2-Ethylhexanoic acid potassium salt

Biodegradability: Readily biodegradable. Information given is based on data obtained from

similar substances.

Biodegradation: 99 % Exposure time: 28 d

Carbon dioxide

Biodegradability: Biodegradation is not applicable.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Biodegradability: Material is not readily biodegradable according to OECD/EEC guidelines.

10-day Window: Fail **Biodegradation:** 0 % **Exposure time:** 28 d

Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Reaction products of phosphoryl trichloride and 2-methyloxirane

Bioaccumulation: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water(log Pow): 2.68 at 30 °C

Page 22 of 28

Product name: FROTH-PAK™ Foam Systems 180 QR POLYOL Revision Date: 25.05.2022 Version: 1.0

trans-1-Chloro-3,3,3-trifluoropropene

Bioaccumulation: No relevant data found.

triethyl phosphate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0.80 Measured

2,2'-oxybisethanol

Bioaccumulation: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water(log Pow): -1.98 at 20 °C

Bioconcentration factor (BCF): 100 Fish Measured

2-Ethylhexanoic acid potassium salt

Bioaccumulation: Bioaccumulation is unlikely. Based on information for a similar material:

Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Carbon dioxide

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0.83 Measured

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Partition coefficient: n-octanol/water(log Pow): 5.503

12.4 Mobility in soil

trans-1-Chloro-3,3,3-trifluoropropene

No relevant data found.

triethyl phosphate

Potential for mobility in soil is very high (Koc between 0 and 50).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient (Koc): 48 Estimated.

2,2'-oxybisethanol

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): < 1 Estimated.

2-Ethylhexanoic acid potassium salt

Based on information for a similar material:

Potential for mobility in soil is very high (Koc between 0 and 50).

Carbon dioxide

No relevant data found.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

No relevant data found.

12.5 Results of PBT and vPvB assessment

Page 23 of 28

Revision Date: 25.05.2022 Version: 1.0

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Reaction products of phosphoryl trichloride and 2-methyloxirane

This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

trans-1-Chloro-3,3,3-trifluoropropene

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

triethyl phosphate

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

2,2'-oxybisethanol

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

2-Ethylhexanoic acid potassium salt

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Carbon dioxide

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

12.6 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Reaction products of phosphoryl trichloride and 2-methyloxirane

No relevant data found.

trans-1-Chloro-3.3.3-trifluoropropene

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

triethyl phosphate

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

2,2'-oxybisethanol

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

2-Ethylhexanoic acid potassium salt

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Carbon dioxide

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Revision Date: 25.05.2022 Version: 1.0

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Do not dump into any sewers, on the ground, or into any body of water. This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

SECTION 14: TRANSPORT INFORMATION

Classification for ROAD and Rail transport (ADR/RID):

14.1 UN number or ID number UN 3500

14.2 UN proper shipping name CHEMICAL UNDER PRESSURE, N.O.S.(Carbon dioxide,

Nitrogen)

14.3 Transport hazard class(es) 2

14.4 Packing group Not applicable

14.5 Environmental hazards Not considered environmentally hazardous based on

available data.

14.6 Special precautions for user

Hazard Identification Number: 20

Classification for SEA transport (IMO-IMDG):

14.1 UN number or ID number UN 3500

14.2 UN proper shipping name CHEMICAL UNDER PRESSURE, N.O.S. (Carbon dioxide,

Nitrogen)

14.3 Transport hazard class(es) 2.2

14.4 Packing group Not applicable

14.5 Environmental hazards Not considered as marine pollutant based on available data.

14.6 Special precautions for user EmS: F-C, S-V

14.7 Maritime transport in bulk

according to IMO Consult IMO regulations before transporting ocean bulk

instruments

Classification for AIR transport (IATA/ICAO):

14.1 UN number or ID number UN 3500

14.2 UN proper shipping name Chemical under pressure, n.o.s.(Carbon dioxide, Nitrogen)

14.3 Transport hazard class(es) 2.2

14.4 Packing group Not applicable

Revision Date: 25.05.2022 Version: 1.0

14.5 Environmental hazards Not applicable **14.6** Special precautions for user No data available.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACh Regulation (EC) No 1907/2006

This product contains only components that have been either registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No. 1907/2006 (REACH)., The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

Restrictions on the manufacture, placing on the market and use:

The following substance/s contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product have to comply with the restrictions placed upon it by the aforementioned provision.

CAS-No.: 68928-76-7	Name: Bis[(2-ethyl-2,5-
	dimethylhexanoyl)oxy](dimethyl)stannane

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

Number on the list: 20

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: Not applicable

Further information

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

Revision Date: 25.05.2022 Version: 1.0

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

Press. Gas - Liquefied gas - H280 - Based on product data or assessment

Acute Tox. - 4 - H302 - Calculation method Eye Irrit. - 2 - H319 - Calculation method Skin Sens. - 1 - H317 - Calculation method

Revision

Identification Number: 12082183 / A670 / Issue Date: 25.05.2022 / Version: 1.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

Europe. Indicative occupational exposure limit values
USA. ACGIH Threshold Limit Values (TLV)
UK. EH40 WEL - Workplace Exposure Limits
Short-term exposure limit (15-minute reference period)
8-hr TWA
USA. Workplace Environmental Exposure Levels (WEEL)
Acute toxicity
Long-term (chronic) aquatic hazard
Serious eye damage
Eye irritation
Gases under pressure
Reproductive toxicity
Skin irritation
Skin sensitisation

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals

Page 27 of 28

Revision Date: 25.05.2022 Version: 1.0

Agency: EC-Number - European Community number: ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS -Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response: GHS - Globally Harmonized System: GLP - Good Laboratory Practice: IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL -No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR -(Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail: SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA -Toxic Substances Control Act (United States): UN - United Nations: vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

SPECIALTY ELECTRONIC MATERIALS UK LIMITED urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

GB