

# Permabond ET5162B

Revision nr.3 Dated 21/02/2025 Printed on 21/02/2025 Page n. 1 / 12

Page n. 1 / 12 Replaced revision:2 (Dated 08/01/2025)

# **Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**District and Country** 

Product name Permabond ET5162B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Adhesive

Identified Uses Industrial Professional Consumer

Use

#### 1.3. Details of the supplier of the safety data sheet

Name Permabond Engineering Adhesives
Full address Niederkasseler Lohweg 18

Niederkasseler Lohweg 18 40547 Düsseldorf

Germany Tel. +44 (0)1962 711 661

e-mail address of the competent person

responsible for the Safety Data Sheet info.europe@permabond.com

Supplier: Permabond Engineering Adhesives Ltd

Wessex Way, Colden Common,

Winchester, Hampshire SO21 1WP, UK

tel: +44 (0)1962 711 661

mail: info.europe@permabond.com

1.4. Emergency telephone number

For urgent inquiries refer to +44 (0)1962 711 661 ( 8.00 am-5.00 pm Mon-Fri)

CHEMTREC UK: +(44)-870-8200418 CHEMTREC Ireland: +(353)-19014670 CHEMTREC Australia: +(61)-290372994 CHEMTREC New Zealand: +(64)-98010034

Tavia if in last al

# **SECTION 2. Hazards identification**

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Acute toxicity, category 3	H331	l oxic if inhaled.
Skin corrosion, category 1	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Specific target organ toxicity - single exposure,	H335	May cause respiratory irritation.
category 3		
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic	H411	Toxic to aquatic life with long lasting effects.
toxicity, category 2		



# Permabond ET5162B

Revision nr.3 Dated 21/02/2025 Printed on 21/02/2025 Page n. 2 / 12

Replaced revision:2 (Dated 08/01/2025)

# SECTION 2. Hazards identification .../>>

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:







Signal words: Danger

Hazard statements:

H331 Toxic if inhaled.

H314 Causes severe skin burns and eye damage.

H335
 H317
 H317
 May cause an allergic skin reaction.
 H411
 Toxic to aquatic life with long lasting effects.

Precautionary statements:

**P273** Avoid release to the environment.

**P280** Wear protective gloves / protective clothing / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice / attention.

**Contains:** 2,2'-DIAMINODIETHYLAMINE

FATTY ACIDS, C18 (UNSATURATED), REACTION PRODUCTS WITH DIETHYLENETRIAMINE

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

## **SECTION 3. Composition/information on ingredients**

### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

2,2'-DIAMINODIETHYLAMINE

INDEX 612-058-00-X 20 ≤ x < 30 Acute Tox. 2 H330, Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B

H314, Eye Dam. 1 H318, STOT SE 3 H335, Skin Sens. 1 H317

EC 203-865-4 LD50 Oral: 1553 mg/kg, LD50 Dermal: 1045 mg/kg, ATE Inhalation vapours:

0,501 mg/l

CAS 111-40-0

FATTY ACIDS, C18 (UNSATURATED), REACTION PRODUCTS WITH DIETHYLENETRIAMINE

INDEX  $10 \le x < 25$  Skin Corr. 1 H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1

H400 M=1, Aquatic Chronic 1 H410 M=1

EC

CAS 1226892-43-8

REACH Reg. 01-2119487013-43-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.



# Permabond ET5162B

Revision nr.3
Dated 21/02/2025
Printed on 21/02/2025
Page n. 3 / 12
Replaced revision:2 (Dated 08/01/2025)

### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

SKIN: Wash skin thoroughly with soap and water. If symptoms occur, seek medical attention. EYES: Be sure to remove any contact lenses before rinsing eyes. Promptly rinse eyes thoroughly with water while holding eyelids open. Continue rinsing for at least 15 minutes. Seek medical attention if discomfort persists. INGESTION: Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Seek medical attention. INHALING: Move exposed person to fresh air. Seek medical attention if symptoms are severe or persistent.

Rescuer protection

Information not available

#### 4.2. Most important symptoms and effects, both acute and delayed

Contact with the skin: skin irritation. Mild dermatitis, allergic rash. Contact with eyes: irritating and can cause redness and pain.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Note for the doctor no specific recommendation. Symptomatic treatment.

Means to have available in the workplace for specific and immediate treatment

Information not available

# **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

# 5.2. Special hazards arising from the substance or mixture

HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE

Avoid breathing combustion products, carbon monoxide (CO), carbon dioxide (CO2), and nitric oxides (NOx).

# 5.3. Advice for firefighters

### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

# **SECTION 6. Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

## 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

## 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb



# Permabond ET5162B

Revision nr.3 Dated 21/02/2025 Printed on 21/02/2025 Page n. 4 / 12 Replaced revision:2 (Dated 08/01/2025)

## SECTION 6. Accidental release measures .../>>

the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

## 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 6.1C

#### 7.3. Specific end use(s)

Adhesive

# **SECTION 8. Exposure controls/personal protection**

### 8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 21.12.2022, 14]
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (IÍ. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
LTU	Lietuva	Jsakymas dėl lietuvos higienos normos hn 23:2011 "cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai" patvirtinimo
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК)



# Permabond ET5162B

Revision nr.3 Dated 21/02/2025 Printed on 21/02/2025 Page n. 5 / 12

Page n. 5 / 12 Replaced revision:2 (Dated 08/01/2025)

# SECTION 8. Exposure controls/personal protection ..../>

ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"

SWE Sverige Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska

gränsvärden (AFS 2018:1)

GBR United Kingdom EH40/2005 Workplace exposure limits (Fourth Edition 2020)

TLV-ACGIH ACGIH 2023

	TT\/ 4 0 ID 0	040 (1110 4 711	D.4.TED\ DE.4.0	TION BROBLE	OTO 14/1TH DI			
			RATED), REAC	TION PRODU	CTS WITH DI	ETHYLENETRIA	MINE	
Predicted no-effect co		- PNEC						
Normal value in fresh	ı water					25,4	mg/l	
Normal value in mari	ne water					2,54	mg/l	
Normal value for fresh water sediment							mg/kg	
Normal value for marine water sediment							mg/kg	
Normal value for water, intermittent release 5,57							mg/l	
Normal value for the	terrestrial co	ompartment				9,44	mg/kg	
-lealth - Derived no-eff	ect level - D	ONEL / DMEL					0 0	
	Effects of	n consumers			Effects on v	vorkers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral		-		-		-		0,25
								mg/kg
								bw/d
Inhalation				0,87				2,9
				mg/m3				mg/m3
Skin				0,25				0,42
				mg/kg bw/d				mg/kg
				2 0				bw/d

2,2'-DIAMINODIETHYLAMINE								
Threshold Limit Value								
Type	Country	TWA/8h	STEL/15min			Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	4						
TLV	CZE	4	0,932	8	1,864			
TLV	DNK	4	1			SKIN		
VLA	ESP	4,3	1			SKIN		
TLV	EST	4,5	1	10	2	SKIN		
VLEP	FRA	4	1					
HTP	FIN	4,3	1	13	3	SKIN		
TLV	GRC	4	1					
AK	HUN	4		8		SKIN		
GVI/KGVI	HRV	4,3	1					
RD	LTU	4,5	1	10	2	SKIN		
TLV	NOR	4	1			SKIN		
TGG	NLD	0,5				SKIN		
NDS/NDSCh	POL	4		12		SKIN		
TLV	ROU	2	0,5	4	1	SKIN		
ПДК	RUS			0,3		п + а, А		
NGV/KGV	SWE	4,5	1	10 (C)	2 (C)	SKIN		
WEL	GBR	4,3	1			SKIN		
TLV-ACGIH		4,2	1			SKIN		

### Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

 $\label{personal protective equipment must be CE marked, showing that it complies with applicable standards.$ 

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends



# Permabond ET5162B

Revision nr.3 Dated 21/02/2025 Printed on 21/02/2025 Page n. 6 / 12 Replaced revision:2 (Dated 08/01/2025)

### SECTION 8. Exposure controls/personal protection

on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Wear a hood visor or protective visor combined with airtight goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. **ENVIRONMENTAL EXPOSURE CONTROLS** 

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

# **SECTION 9. Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Properties		Value		Information		
Appearance		paste				
Colour		white				
Odour		mild				
Melting point / freezing point		not available				
Initial boiling point		not available				
Flammability		not available				
Lower explosive limit		not available				
Upper explosive limit		not available				
Flash point	>	100	°C			
Auto-ignition temperature		not available				
Decomposition temperature		not available				
рН		not available		Reason for missing	data:substa	nce/mixture is
				non-soluble	(in	water)
Kinematic viscosity		not available				
Dynamia viagosity						
Dynamic viscosity		~ 19000 mPa.	S	Temperature: 23 °C		
Solubility		~ 19000 mPa. not available	s	Temperature: 23 °C		
,			s	Temperature: 23 °C		
Solubility		not available	s	Temperature: 23 °C		
Solubility Partition coefficient: n-octanol/water		not available not available	s	Temperature: 23 °C		
Solubility Partition coefficient: n-octanol/water Vapour pressure		not available not available not available	s	Temperature: 23 °C		
Solubility Partition coefficient: n-octanol/water Vapour pressure Density and/or relative density		not available not available not available 1,2		Temperature: 23 °C		

### 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

# **SECTION 10. Stability and reactivity**

### 10.1. Reactivity

The following materials may react with the product: Strong oxidizing agents, Reducing agents, strong acids and bases.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.



# Permabond ET5162B

Revision nr.3 Dated 21/02/2025 Printed on 21/02/2025 Page n. 7 / 12

Page n. 7 / 12 Replaced revision:2 (Dated 08/01/2025)

# SECTION 10. Stability and reactivity .../>>

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid

Stable under normal conditions of storage and use.

Protect from direct sunlight.

Avoid contact with acids and oxidizing agents.

#### 10.5. Incompatible materials

See the reactivity section.

#### 10.6. Hazardous decomposition products

By thermal decomposition, carbon monoxide, carbon dioxide and ed other unidentified organic compounds.

# **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

# ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:

ATE (Oral) of the mixture:

>2,09 mg/l

>2000 mg/kg

ATE (Dermal) of the mixture:

>2000 mg/kg

FATTY ACIDS, C18 (UNSATURATED), REACTION PRODUCTS WITH DIETHYLENETRIAMINE

LD50 (Oral): > 2000 mg/kg

2,2'-DIAMINODIETHYLAMINE

 LD50 (Dermal):
 1045 mg/kg Rabbit

 LD50 (Oral):
 1553 mg/kg Rat

 LC50 (Inhalation vapours):
 0,3 mg/l/4h Rat

ATE (Inhalation vapours): 0,501 mg/l estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage



# Permabond ET5162B

Revision nr.3 Dated 21/02/2025 Printed on 21/02/2025 Page n. 8 / 12

Page n. 8 / 12 Replaced revision:2 (Dated 08/01/2025)

# SECTION 11. Toxicological information .../>>

### RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

May cause respiratory irritation

### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## **SECTION 12. Ecological information**

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

# 12.1. Toxicity

FATTY ACIDS, C18 (UNSATURATED), REACTION PRODUCTS WITH DIETHYLENETRIAMINE

 LC50 - for Fish
 0,19 mg/l/96h

 EC50 - for Crustacea
 0,18 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 47,6 mg/l/72h

 EC10 for Algae / Aquatic Plants
 323,8 mg/l/72h

 Chronic NOEC for Crustacea
 25,5 mg/l

# 12.2. Persistence and degradability

2,2'-DIAMINODIETHYLAMINE

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

### 12.3. Bioaccumulative potential

2,2'-DIAMINODIETHYLAMINE

Partition coefficient: n-octanol/water -5,58

# 12.4. Mobility in soil

2,2'-DIAMINODIETHYLAMINE

Partition coefficient: soil/water 3.4

# 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.



# Permabond ET5162B

Revision nr.3 Dated 21/02/2025 Printed on 21/02/2025 Page n. 9 / 12 Replaced revision:2 (Dated 08/01/2025)

# SECTION 12. Ecological information ..../>>

### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

## **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

**CONTAMINATED PACKAGING** 

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Waste class 08 04 09\* stickers and sealed sealing, containing organic solvents or other dangerous substances.

# **SECTION 14. Transport information**

#### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 3267

### 14.2. UN proper shipping name

ADR / RID: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (2,2'-DIAMINODIETHYLAMINE; FATTY ACIDS, C18

(UNSATURATED), REACTION PRODUCTS WITH DIETHYLENETRIAMINE)

IMDG: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (2,2'-DIAMINODIETHYLAMINE; FATTY ACIDS, C18

(UNSATURATED), REACTION PRODUCTS WITH DIETHYLENETRIAMINE)

IATA: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (2,2'-DIAMINODIETHYLAMINE; FATTY ACIDS, C18

(UNSATURATED), REACTION PRODUCTS WITH DIETHYLENETRIAMINE)

### 14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8

IMDG: Class: 8 Label: 8

IATA: Class: 8 Label: 8



### 14.4. Packing group

ADR / RID, IMDG, IATA:



# Permabond ET5162B

Revision nr.3 Dated 21/02/2025 Printed on 21/02/2025 Page n. 10 / 12 Replaced revision:2 (Dated 08/01/2025)

### SECTION 14. Transport information .../>>

#### 14.5. Environmental hazards

ADR / RID: Environmentally Hazardous

IMDG: Marine Pollutant

IATA: Environmentally Hazardous



For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

#### 14.6. Special precautions for user

ADR / RID: HIN - Kemler: 80 Limited Quantities: 1 lt Tunnel restriction code: (E)

Special provision: 274

IMDG: EMS: F-A, S-B Limited Quantities: 1 lt IATA: Cargo: Maximum quantity: 30 L

Cargo: Maximum quantity: 30 L Packaging instructions: 855 Passengers: Maximum quantity: 1 L Packaging instructions: 851

Special provision: A3, A803

### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

# **SECTION 15. Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: H2-E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3
Contained substance
Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

#### ΕN



# **Permabond Engineering Adhesives**

# Permabond ET5162B

Revision nr.3 Dated 21/02/2025 Printed on 21/02/2025 Page n. 11/12 Replaced revision:2 (Dated 08/01/2025)

# SECTION 15. Regulatory information .../>>

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

## **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2
Acute Tox. 3
Acute Tox. 4
Skin Corr. 1B
Skin Corr. 1
Eye Dam. 1

Acute Tox. 2
Acute toxicity, category 3
Acute toxicity, category 4
Skin corrosion, category 1B
Skin corrosion, category 1
Serious eye damage, category 1

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Skin Sens. 1Skin sensitization, category 1Skin Sens. 1ASkin sensitization, category 1A

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

H330 Fatal if inhaled.
H331 Toxic if inhaled.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.

**H314** Causes severe skin burns and eye damage.

H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.

**H400** Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

Regulation (EC) 1907/2006 (REACH) of the European Parliament



# Permabond ET5162B

Revision nr.3 Dated 21/02/2025 Printed on 21/02/2025 Page n. 12 / 12 Replaced revision:2 (Dated 08/01/2025)

#### SECTION 16. Other information .../>>

- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

#### Changes to previous review:

The following sections were modified:

12 / 13 / 14.